


SMD 32.768kHz Crystal Oscillators

7A Series SMD 7050 32.768kHz Crystal Oscillator 32.768kHz O: CMOS Size: 7.0×5.0×1.4mm



Features


- 7050 size, 1.4mm high. Miniature and lightweight SMD 32.768kHz crystal oscillators
- 3-state function
- Supply voltage: 1.8V~3.3V
- 32.768kHz reference frequency output
- Low jitter provides for high performance
- Application for RTC reference clock, Wearable device, RTC module, IoT, Health and wellness monitors, Watch, etc
- RoHS Compliant /Pb Free



Standard Specifications

Item	Type	7A Series SMD 3225 32.768kHz Crystal Oscillator
Output Type		CMOS
Load condition		15pF, or specify
Frequency Range		32.768kHz
Supply Voltage		1.8V~3.3V
Frequency Stability (All Condition)		±20ppm, ±25ppm, ±30ppm, ±50ppm, or specify
Current Consumption		60μA max.
Stand-by Current		3μA max.
Symmetry		45~55%
0 Level Output Voltage (V _{OL})		0.1V _{cc} max.
1 Level Output Voltage (V _{OH})		0.9V _{cc} min.
Rise Time / Fall Time		12ns max.
OE Pin 0 Level Input Voltage (V _{IL})		0.2V _{cc} max.
OE Pin 1 Level Input Voltage (V _{IH})		0.8V _{cc} min.
Start-up Time		5ms max.
Operating Temperature Range		-20~+70°C, -40~+85°C, or specify
Storage Temperature Range		-55~+125°C
Phase Jitter (12KHz~20MHz)		1ps max.

Dimensions



Recommended Land Pattern [mm]

